

MODEL 115 H.O. - V4

SPECIFICATIONS



| | |
|-------------------------------|---|
| Model | a. E115DHL b. E115HSL c. E115DHX |
| Shaft Length mm (in) / Color | a. 508 (20") Blue b. 508 (20") White c. 635 (25") Blue |
| Weight kg (lbs) | a. / b. 177 (390) c. 184 (405) |
| Engine Type | Loop Charged V4 60° E-TEC Direct Injection |
| Bore x Stroke mm (in) | 91 x 66 (3.600 x 2.588) |
| Displacement cc (cu in) | 1727 (105.4) |
| Ignition System | IDI Fast Rise Inductive Ignition |
| Starter | Electric |
| Trim Method | FasTrak™ Power Trim and Tilt |
| Propshaft kilowatts (HP)* | 86 kw (115 HP) @ 5750 RPM |
| Full Throttle Operating Range | 5500-6000 RPM |
| Gear Ratio | a. / b. 2.0:1 c. 2.25:1 |
| Fuel Induction | E-TEC Direct Fuel Injection with stratified low RPM combustion mode |
| Alternator | Variable Voltage Computer Controlled 133 Amp** / 1800 watt output with Regulator |
| Cooling | Pressure and Temperature Controlled Water Cooled |
| Steering | Remote or Accessory Tiller |
| Limited Warranty | 3 Years Non-Declining |
| Emissions Compliance | EPA CARB 3 STAR European Union |



* Power Ratings: Evinrude® outboards are power rated in accordance with NMMA procedure using the International Council of Marine Industry Associates (ICOMA) standard 28/83.

** 133 Amp current calculated at 13.5 V. Net dedicated battery charging power output is 50 Amp.