

MODEL 250 V6

SPECIFICATIONS



Model	a. E250DPL b. E250DPX c. E250DCX d. E250DPZ e. E250DCZ
Shaft Length mm (in) / Color	a. 508 (20") Blue b. / c. 635 (25") White d. / e. 762 (30") White
Weight kg (lbs)	a. 235 (518) b. / c. 238 (524) d. / e. 240 (530)
Engine Type	Loop Charged V6 90° E-TEC Direct Injection
Bore x Stroke mm (in)	98 x 73 (3.854 x 2.858)
Displacement cc (cu in)	3279 (200)
Ignition System	IDI Fast Rise Inductive Ignition
Starter	Electric
Trim Method	FasTrak™ Power Trim and Tilt
Propshaft kilowatts (HP)*	187 kw (250 HP) @ 5150 RPM
Full Throttle Operating Range	4500-5800 RPM
Gear Ratio	1.85:1
Fuel Induction	E-TEC Direct Fuel Injection with stratified low RPM combustion mode
Alternator	Variable Voltage Computer Controlled 133 Amp** / 1800 watt output with Regulator
Cooling	Pressure and Temperature Controlled Water Cooled
Steering	Remote
Limited Warranty	3 Years Non-Declining
Emissions Compliance	EPA CARB 3 STAR European Union



* Power Ratings: Evinrude® outboards are power rated in accordance with NMMA procedure using the International Council of Marine Industry Associates (ICOMA) standard 28/83.

** 133 Amp current calculated at 13.5 V. Net dedicated battery charging power output is 50 Amp.