

MODEL 65 COMMERCIAL

SPECIFICATIONS



Model	a. E65WDRL b. E65WDRY
Shaft Length mm (in) / Color	a. 508 (20") Blue b. 572 (22.50") Blue
Weight kg (lbs)	a. 107 (235) b. 109 (240)
Engine Type	Inline 2-cylinder E-TEC Direct Injection
Bore x Stroke mm (in)	91 x 66 (3.600 x 2.588)
Displacement cc (cu in)	863 (52.7)
Ignition System	IDI Fast Rise Inductive Ignition
Starter	Manual Rope
Trim Method	Manual tilt w/ tilt assist cylinder
Propshaft kilowatts (HP)*	48.5 kw (65 HP) @ 5750 RPM
Full Throttle Operating Range	5500-6000 RPM
Gear Ratio	2.67:1
Fuel Induction	E-TEC Direct Fuel Injection with stratified low RPM combustion mode
Alternator	Variable Voltage Computer Controlled 81 Amp** / 1100 watt output with Regulator
Cooling	Pressure and Temperature Controlled Water Cooled
Steering	Tiller Standard
Limited Warranty	1 Year Non-Declining
Emissions Compliance	EPA CARB 2 STAR European Union



* Power Ratings: Evinrude® outboards are power rated in accordance with NMMA procedure using the International Council of Marine Industry Associates (ICOMA) standard 28/83.

** 81 Amp current calculated at 13.5 V. Net dedicated battery charging power output is 25 Amp.