

## MODEL 75 SPECIFICATIONS



Model	a. E75DPL b. E75DSL
Shaft Length mm (in) / Color	a. 508 (20") Blue b. 508 (20") White
Weight kg (lbs)	145 (320)
Engine Type	Inline 3-cylinder E-TEC Direct Injection
Bore x Stroke mm (in)	91 x 66 (3.600 x 2.588)
Displacement cc (cu in)	1295 (79)
Ignition System	IDI Fast Rise Inductive Ignition
Starter	Electric
Trim Method	FasTrak™ Power Trim and Tilt
Propshaft kilowatts (HP)*	56 kw (75 HP) @ 5000 RPM
Full Throttle Operating Range	4500-5500 RPM
Gear Ratio	2.0:1
Fuel Induction	E-TEC Direct Fuel Injection with stratified low RPM combustion mode
Alternator	Variable Voltage Computer Controlled 81 Amp** / 1100 watt output with Regulator
Cooling	Pressure and Temperature Controlled Water Cooled
Steering	Remote or Accessory Tiller
Limited Warranty	3 Years Non-Declining
Emissions Compliance	EPA CARB 3 STAR European Union



\* Power Ratings: Evinrude® outboards are power rated in accordance with NMMA procedure using the International Council of Marine Industry Associates (ICOMA) standard 28/83.

\*\* 81 Amp current calculated at 13.5 V. Net dedicated battery charging power output is 25 Amp.